



TERPEL SAE 15W40 CI-4 PLUS/SL

DESCRIPTION:

- Premium grade diesel engine oil that provides excellent protection for newer, high performance engines that are used in the toughest on road and off road applications.
- Shown to be versatile as well as able to meet the grueling demands of today's low emission diesel engines, as well as the older models which are using both low and high sulfur fuels.
- Recommended for use in a variety of heavy duty uses as well as operating environments.
- Meets the API SL specification for gasoline engines that are used in mixed fleets.

FEATURES/BENEFITS:

- Performs well in low emission diesel engines which increase the demands on engine lubricants.
- Delivers the best performance in these late model engines, as well as older engines.
- Excellent soot handling capabilities.
- Exemplary thermal stability and oxidation control.
- Contains properties which provide anti-wear and anti-scuff.
- Contains extended TBN reserves which provide improved acid neutralization and corrosion protection.
- Maximizes oil flow to the critical bearing surfaces during start up.
- Has Stay-in-grade shear stability.
- Extended drain capabilities- excellent water tolerance.
- Excellent deposit control, oil oxidation resistance, wear and rust control in gasoline and diesel engines.

APPLICATIONS:

- On the highway applications for light and heavy duty trucking.
- Off the highway applications such as trucking, construction, agriculture and quarrying.
- Various mixed fleet applications.

Meets performance requirements :

- API CI-4 PLUS, CI-4, CH-4, CF-4, CF/SL, SJ, SH
- ACEA E7, E6, E5, E4, E3,
- ACEA A3/B4, A3/B3
- JASO DH-1, Category DHD-1
- MACK EO-M PREMIUM PLUS 03, Mack EO-N, Mack EO-M Plus, MACK EO-L
- CUMMINS CES 20071, 20076, 20078, 20078,
- Allison C3, C4, TO-2
- DETROIT DIESEL 93k214, 72 SE 270,
- FORD M2C153G
- VOLVO VDS-3, VDS-2, VDS,
- CATERPILLAR ECF-1, ECF-2, S-3, TO-2
- MB 228.0, MB 228.3
- MAN 271, 3275

TYPICAL DATA TEST

| SAE GRADE | 15W40 |
|-----------------------------------|-------------|
| Specific Gravity, (60°F) | 0.8770 |
| Viscosity, Kinematic @ 40°C, cSt | 104.7 |
| Viscosity, Kinematic @ 100°C, cSt | 14.0 |
| Viscosity Index | 135 |
| Cold Crank, cP at °C, Max | 7000 @ -20C |
| Flash Point, °F | 425 |
| Pour Point, °C(°F) | -21 (-5.8) |
| Color, Max | 4.5 |
| TBN | 12 |
| Sulfated Ash, wt% | 1.5 |

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.