



TERPEL SAE 25W-60 API CH-4/SL

DESCRIPTION:

Terpel SAE 26W-60 provides high quality engine protection under all driving conditions and is specifically formulated to provide extra protection against the harmful effects of city driving.

This oil has a low friction formula that helps improve gas mileage, extend engine life and helps protect against rust, corrosion, startup wear and varnish build-up. It also protects against thermal breakdown which helps prevent stuck rings.

BENEFITS:

- Protects engines under all driving conditions.
- Lowers friction and improves gas mileage.
- Provides longer engine life.
- Protects against rust, corrosion and varnish.
- Resiste la descomposición térmica.
- Resists thermal break-down.

APLICACIONES:

Terpel SAE 25W-50 has a good performance on the highway applications for light and heavy-duty trucking and in off the highway applications such as trucking, construction, agriculture and quarrying. Also it can be used in various mixed fleet applications.

***Meets the requirements and especifications of:**

- API CH-4/SL

*ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

***TYPICAL TEST DATA:**

PROPERTIES	RESULTS
Specific Gravity, (60°F)	0.8909
Viscosity, @ 40°C, cSt	232.7
Viscosity, @ 100°C, cSt	127
Viscosity Index	108
CCT, cP at °C, Max	13,000 @ -10C
Flash Point, °F	398
Pour Point, °C(°F)	-23 (-9)
Color,	VERDE
TBN	8.0

* Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.