



SYNTHETIC BLEND SAE 15W40 CK-4/SN

DESCRIPTION

- Specially formulated to ensure superior lubrication and long life.
- Premium grade diesel engine oil that provides protection and oxidation resistance for highly rated diesel engines running in severe service conditions.
- Shown to be versatile as well as able to meet the grueling demands of today's low emission diesel engines, as well as the older models which are using both low and high sulfur fuels.
- Recommended for use in a variety of heavy duty uses as well as operating environments.

FEATURES/BENEFITS:

- Performs well in low emission diesel engines which increase the demands on engine lubricants.
- Delivers the best performance in late model engines as well as older engines.
- Excellent soot handling capabilities.
- Exemplary thermal stability and oxidation control.
- Contains properties which provide anti-wear and anti-scuff.
- Contains extended TBN reserves which provide improved acid neutralization and corrosion protection.
- Maximizes oil flow to the critical bearing surfaces during start up.
- Has stay-in-grade shear stability.
- Extended drain capabilities- excellent water tolerance.

APPLICATIONS:

- On the highway applications for light and heavy duty trucking.
- Off the highway applications such as trucking, construction, agricultura and quarrying.
- Various mixed fleet applications.

Meets Performance Requirements:

- API CK-4, CJ-4, CI-4 PLUS, CH-4
 - API SN, SM, SL
 - CUMMINS CES 20086
 - MACK EOS 4.5
 - MB 228.31
 - DDC 93K222
 - CATERPILLAR ECF-3
- VOLVO VDS 4.5
RENAULT VI RLD-4
MTU TYPE 2.1
DEUTZ DQC III-10 LA
FORD WSS-M2C171-F1
MAN 3575
ACEA E9-16

TYPICAL TEST DATA

SAE GRADE	15W40
Specific Gravity @ 60°F	0.8731
Viscosity, Kinematic	
cSt @ 40°C	116.30
cSt @ 100°C	15.4
Viscosity Index	139
Flash Point, (°F)	400
Pour Point, °C(°F)	-36 (-32.8)
Cold Crank, cP at -20°C	5,440
Color	5.5
TBN	10

Typical test data are average values only. Minor variations wich do not affect product performance are to be expected during normal manufacturing.